PDF Download

Machinery>
Tablet coating>
SMARTCOATER X• ONE series

SMARTCOATER 1400 X-ONE

About the SMARTCOATER X•ONE series

Backed by more than 60 years of ACG engineering expertise, the SMARTCOATER X•ONE incorporates everything you need to ensure swift and economical processes – and uphold consistently high standards. As part of our new X•ONE series, and the next-level upgrade of ACG's premium tablet-coating system, it makes tablet coating extraordinarily fast and fully reassuring, with increased process speed, efficiency and usability.

About the SMARTCOATER 1400 X•ONE

Developed to bring design and technology into perfect harmony, this is a genuinely smart machine with an elegant aesthetic, and handles batches up to 1400 litres... effortlessly.

Applications

Film coating, seal coating, sugar coating, drug coating of tablets, micro-tablet coating, pellet coating

Features	Benefits	
Unique coating system that includes baffles, spray arms and drum	Flexibility to work with 10-100% batch occupancy	
High-performing spray-arm design with full external control via infinity handle	Accurate bed coverage for the entire batch size and can be positioned to match all product requirements Avoids delays caused by in-process intervention	
ACG's X•ONE 2.0 Spray Nozzle developed in collaboration with Dusen-Schlick, Germany with an Anti-Bearding Cap – now 50% lighter	No product build-up, so far easier to clean and maintain Easier handling	
Modular, automated and integrated design for tablet charging and discharging with inbuilt discharge baffles	Dust-free, closed-door charging and 100% tablet discharge	
Advanced wash-in-place (WIP) technology featuring the optimum number and arrangement of nozzles	Complete wetting of dead spots for faster, safer and efficient washing of all parts – including extreme corners	
ACG's exclusive X•ONE command and control system	Compliant with ATEX, GAMP 5 and 21 CFR Part 11, this advanced technology allows intuitive, secure monitoring and control	

Technical specifications

SMARTCOATER 1400 X•ONE					
		Tablet coating	Micro-tablet coating	Pellet coating	
Working capacity	Min	1401*	5601	7001	
	Max	14001	11201	11201	

^{*}For select formulations only.

Commented [AS1]: Hyperlink it to X•ONE 2.0 Spray
Nozzle